


u-blox M8 ADR modules including 3D sensors

Highlights

- Leading performance under poor signal conditions
- Continuous navigation during signal loss
- Complete solution with integrated 3D sensors
- Automatic configuration of wheel-tick/speed input
- Real-time positioning up to 20 Hz rate
- GPS/QZSS, GLONASS, BeiDou, Galileo
- Zero PPM program for automotive grade NEO-M8L-01A



NEO-M8L
12.2 x 16.0 x 2.4 mm

Product description

The NEO-M8L 3D Automotive Dead Reckoning (ADR) modules combine GNSS, inertial sensing, and speed information from the vehicle to provide continuous and accurate 3D positioning for road vehicles.

Incorporating u-blox's latest advancements in multi-GNSS signal processing (now including Galileo), the latest version of NEO-M8L delivers the ideal solution where navigation performance is the priority, regardless of GNSS signal quality or availability. In addition to the on-board sensors, NEO-M8L further eases installation with automatic configuration of speed or wheel-tick inputs, and compensation for in-vehicle antennas.

The intelligent combination of GNSS and sensor measurements enables accurate, real-time positioning, speed and heading information at rates up to 20 Hz, as essential for smooth and responsive interactive display. Access to native, high rate sensor data enables host applications to make full use of the receiver's assets.

The NEO-M8L includes u-blox's latest generation GNSS technology which adds Galileo to the multi-constellation reception that already includes GPS, GLONASS, BeiDou and QZSS. The module provides high sensitivity and fast GNSS signal acquisition and tracking.

UART, USB, DDC (I²C compliant) and SPI interface options provide flexible connectivity and enable simple integration with most u-blox cellular modules.

NEO-M8L modules use GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

The NEO-M8L-01A automotive grade module adheres to automotive industry standard quality specifications and production flow.

Product selector

| Model | Category | GNSS | | | | Supply | Interfaces | Features | | | | Grade |
|--------------------|-------------------------|------------|---------|---------|--------|---------------------------|------------|---------------|------|-----|-----|----------------------|
| | Standard Precision GNSS | GPS / QZSS | GLONASS | Galileo | BeiDou | Number of Concurrent GNSS | | 2.7 V – 3.6 V | UART | USB | SPI | Programmable (Flash) |
| NEO-M8L-0 | ADR | • | • | • | • | 3 | • | • | • | • | • | • |
| NEO-M8L-01A | ADR | • | • | • | • | 3 | • | • | • | • | • | • |

ADR = Automotive Dead Reckoning / UDR = Untethered Dead Reckoning

C = Crystal / T = TCXO

Features

| | |
|--------------------|---|
| Receiver type | 72-channel u-blox M8 engine GPS/QZSS L1 C/A, GLONASS L10F, BeiDou B1I, Galileo E1B/C SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN |
| Nav. update rate | Up to 20 Hz |
| Position accuracy | 2.0 m CEP |
| ADR position error | (Estimated) 2 % of distance travelled without GNSS |
| Acquisition | Cold starts: 26 s Aided starts: 3 s Reacquisition: 1 s |
| Sensitivity | Tracking & Nav: -160 dBm ¹ Cold starts: -148 dBm Hot starts: -157 dBm |
| Assistance | AssistNow GNSS Online AssistNow GNSS Offline (up to 35 days) AssistNow Autonomous (up to 6 days) OMA SUPL & 3GPP compliant |
| Oscillator | Crystal |
| RTC | Built-in |
| Sensor | Onboard 3D accelerometer and 3D gyroscope |
| Supported antennas | Active or passive antenna |
| Raw Data | Code phase output |
| Navigation outputs | Position, speed, acceleration, heading, heading rate, attitude, time |
| Data-logger | For position, velocity, time, and odometer data |

¹ Limited by FW for best DR performance

Electrical data

| | |
|-------------------|--|
| Supply voltage | 2.7 V to 3.6 V |
| Power consumption | 29 mA @ 3.0 V (Continuous, default concurrent mode) |
| Backup Supply | 1.4 to 3.6 V |

Interfaces

| | |
|-------------------|---|
| Serial interfaces | 1 UART 1 USB V2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I ² C compliant) |
| Digital I/O | Configurable timepulse |
| Timepulse | Configurable 0.25 Hz to 10 MHz |
| Protocols | NMEA, UBX binary, RTCM |

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is" and u-blox assumes no liability for the use of the information. No warranty, either express or implied, is given, including but not limited, with respect to the accuracy, correctness, reliability and fitness for a particular purpose of the information. This document may be revised by u-blox at any time. For most recent documents, visit www.u-blox.com.

Copyright © 2016, u-blox AG

Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4 mm

Pinout



Environmental data, quality & reliability

Operating temp. -40° C to 85° C

Storage temp. -40° C to 85° C

RoHS compliant (lead-free)

Qualification according to ISO 16750

Manufactured and fully tested in ISO/TS 16949 certified production sites

Uses u-blox M8 chips qualified according to AEC-Q100

Support products

u-blox M8 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox M8 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-M8L u-blox M8 3D Dead Reckoning GNSS Evaluation Kit; supports NEO-M8L modules

Product variants

| | |
|-------------|--|
| NEO-M8L-0 | u-blox M8 GNSS LCC module with 3D Dead Reckoning and onboard sensors, Professional Grade |
| NEO-M8L-01A | u-blox M8 GNSS LCC module with 3D Dead Reckoning and onboard sensors, Automotive Grade |

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.